

Machinability will supply the right equipment for all your salting and snow plowing requirements.

Agricultural Tractors • Loaders • Skid Steers

| | Width | Capacity |
|--------------|-------|----------|
| Model | (in) | cu.yd |
| 1 cu.yd | 48 | 1 |
| 2 cu.yd | 48 | 2 |

All specifications are approximate. Machinability reserves the right to make changes in specifications and/or improvements at any time without obligation or notice.

View our full product line at www.machinability.com:



Power Sidewing Plow
Series SW-48



V-Plow
Series V-48



Trip Moldboard Plow
Series STM-35/STM-28



Drop Salter



QUALITY DOESN'T COST. IT PAYS.

1515 Rebecca Street, P.O. Box 60011
Oakville, Ontario CANADA L6L 6R4
www.machinability.com • 1-877-321-2282



TOW BEHIND SALTER

QUALITY DOESN'T COST. IT PAYS.



Tow Behind Salter

Sizes 1cu.yd and 2cu.yd

MACHINABILITY

TOW BEHIND SALTER

Indispensible Features

Machinability's tow behind salter is another example of the new standards of quality in the industry. The fit, finish, and structural integrity are second to none in the market. Inquire to Machinability directly by phone, or contact your closest dealer for current pricing.

Cutting-Edge Design:

By combining unsurpassed strength and weight saving construction, we have the right product for your application. By utilizing modular design, we can configure the trailer to meet your specific applications and requirements. All hydraulics can be controlled manually to help you optimize your deposition rate and spread pattern.

| Feature | 1 cu.yd | 2 cu.yd |
|---|---------|---------|
| 1 Capacity (to top of box) | 1 cu.yd | 2 cu.yd |
| 2 Hot dipped galvanized box | ✓ | ✓ |
| 3 Liquid Ready (Pre-Wet spray and Anti-Icing). All Compu Spread components. | ✓ | ✓ |
| 4 Optional anti-icing tank fits inside main box | 300 gal | 600 gal |
| 5 3500 lb axle with electric brakes on each axle | Single | Duel |
| 6 Optional replaceable 5200 lb axle for greater hauling capacity | Single | Duel |
| 7 Pivoting hitch available with pintle eye for zero tongue load | ✓ | ✓ |
| 8 Front or rear mounted spinner with the same unit | ✓ | ✓ |
| 9 Optional salt box lid with safety lock out | ✓ | ✓ |

| Feature | 1 cu.yd | 2 cu.yd |
|---|---------|---------|
| 10 Adjustable spinner location and speed to optimize spread patter | ✓ | ✓ |
| 11 Pre-Wet flow rate related to variable chain speed | ✓ | ✓ |
| 12 Hand crank adjustable gate to equalize salt distribution over the spinner | ✓ | ✓ |
| 13 Easy to adjust and lock chain tensioner | ✓ | ✓ |
| 14 Replaceable bumper | ✓ | ✓ |
| 15 Removable rubber skirt flap to control spread on sidewalks or for broadcasting | ✓ | ✓ |
| 16 Overrated gearbox, salt water tested for 1000 h | ✓ | ✓ |
| 17 All hydraulic and electrical lines guarded | ✓ | ✓ |
| 18 LED lights meet SAE standards, and are shielded from the salt when loading | ✓ | ✓ |
| 19 Optional strobe lighting | ✓ | ✓ |
| 20 Hand Brake | ✓ | ✓ |



Tow Behind Salter

Sizes 1cu.yd and 2cu.yd